

SAFETY DATA SHEET

American Paint Recyclers LLC
1235 Industrial Drive
Van Wert, Ohio 45891

INFORMATIONAL TELEPHONE NUMBER:
1-888-978-6558

Preparation Date: 12/1/2016

WEBSITE:
www.AmericanPaintRecyclers.com

SECTION 1 – PRODUCT INFORMATION

NAME: EcoTone Paint – Water-based, recycled latex paint

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDS STATEMENT:

Causes Mild Skin and Eye Irritations

Precautionary Statements:

Wear Eye and Face Protection

Eye Contact: Rinse with Water for 15 Minutes

Skin Contact: Wash Thoroughly with Soap and Water

If Eye or Skin Irritation Persists, Seek Medical Attention

KEEP OUT OF REACH OF CHILDREN

HMIS Codes

Health	1
Flammability	0
Reactivity	0

PRECAUTIONARY STATEMENTS:

Wear Eye and Face Protection

Eye Contact: Rinse with Water for 15 Minutes

Skin Contact: Wash Thoroughly with Soap and Water

If Eye or Skin Irritation Persists, Seek Medical Attention

KEEP OUT OF REACH OF CHILDREN



SECTION 3 – HAZARDS IDENTIFICATION

% by Weight	CAS Number	Ingredient	Units	Vapor Pressure
.0003%	10377-60-3	Magnesium Nitrate		
.00002%	26172-55-4	5-Chloro-2-methyl-4-isothiazolin-3-one		
>.00001%	2682-20-4	2-Methyl-4-isothiazolin-3-one		
>.00001%	3251-23-8	Nitric acid, copper (2+) salt (2:1)		
.001%	1336-21-6	Ammonium hydroxide		

NOTE: This product consists primarily of post-consumer recycled latex paints from various manufacturers. The composition of each batch may vary with feedstocks.

SECTION 4 – FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention.

SKIN: Wash thoroughly with soap and water. Remove any contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure and move to fresh air. Call for emergency medical care.

INGESTION: If swallowed, do not induce vomiting. Have victim drink enough fresh water to ensure dilution. Seek medical attention.

SECTION 5 – FIRE FIGHTING MEASURES

FLASH POINT: Not applicable **LEL:** Not applicable **UEL:** Not applicable

FLAMMABILITY CLASSIFICATION: Not applicable

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Closed containers may explode (due to pressure build up) when exposed to extreme heat.

During emergency conditions overexposure to decomposition products may cause a health hazard.

Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES:

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible automatic ignition or explosion.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Ventilate the area. Remove with inert absorbent.

SECTION 7 – HANDLING AND STORAGE

STORAGE CATEGORY: Not applicable

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:

Keep container closed when not in use. Do not expose to freezing temperatures. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of reach of children.

SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN:

Use only with adequate ventilation.

Avoid contact with skin and eyes.

Wash hands after using.

VENTILATION: Local mechanical exhaustion should be used to dissipate vapors. Open doors and windows, and use fans to exhaust vapors.

RESPIRATORY PROTECTION: For spray applications, use properly fitted organic vapor/particulate respirator. When sanding or abrading the dried film, wear a dust respirator for dust which may be generated from the product, underlying paint, or the abrasive.

PROTECTIVE GLOVES: Use waterproof gloves to avoid skin contact.

EYE PROTECTION: Use safety glasses with non-perforated side shields, face shield, or goggles.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE: 212-225 Degree Fahrenheit

MELTING POINT: Not available

EVAPORATION RATE: Slower Than Ether

SPECIFIC GRAVITY: 1.4

VAPOR DENSITY: Heavier Than Air

SOLUBILITY IN WATER: Partly Soluble

APPEARANCE AND ODOR: Mild latex and ammonia odor.

SECTION 10 – STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID:

Avoiding storage below 40 degrees. Avoid use of product below 50 degrees.

HAZARDOUS DECOMPOSITION PRODUCTS:

By Fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION:

Will not occur

SECTION 11 – TOXICOLOGICAL INFORMATION

INHALATION: Prolonged exposure to vapor may irritate respiratory system. Dizziness, headache, and nausea may also result.

EYE CONTACT: Direct contact may cause eye irritation and redness.

SKIN CONTACT: Prolonged contact with skin may cause irritation and redness.

INGESTION: May cause nausea, vomiting, and diarrhea.

SECTION 12 – ECOLOGICAL INFORMATION

ECOTOXICOLOGY INFORMATION:

No data available.

SECTION 13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD:

Waste from this product is not hazardous. Collect contaminated materials into an appropriate container. Dispose of in accordance with Federal, State, and Local regulations regarding pollution.

SECTION 14 – TRANSPORT INFORMATION

All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. Do not expose product to temperatures below 40 degrees for an extended period of time. Acceptable for ground and air transport as non-hazardous material.

SECTION 15 – REGULATORY INFORMATION

Contains less than 150 g/L of VOCs per VOC content limits for architectural and industrial maintenance (AIM) coatings per U.S. EPA Standards.

SECTION 16 – OTHER INFORMATION

LATEST REVISION: 12/1/2016

DISCLAIMER: THE INFORMATION CONTAINED HEREIN HAS BEEN OBTAINED BY RELIABLE SOURCES, BUT IS FURNISHED BY AMERICAN PAINT RECYCLERS LLC WITHOUT WARRANTY (EXPRESSED OR IMPLIED) AS TO THE ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR CIRCUMSTANCES.